



Galvanized steel fasteners and connectors, sealed within a rubberized PVC skin. Storm Greeter is made to last through the everyday exposure to salt spray and humidity, the chemicals in treated lumber, and to replace the rusting connectors that may not last through the next year...or the next big storm.

Framing – Structural Applications

| Part Name | SG Part No. | Simpson # | USP # | |
|---------------------------|-------------|-----------|-------------|--|
| Hurricane Strap 18" | HS-18 | LSTA18 | LSTA/MSTA18 | Hurricane Straps & Ties Hurricane Straps & Ties are made for |
| Hurricane Strap 24" | HS-24 | LSTA24 | LSTA/MSTA24 | protecting structures from the uplift caused by high winds - along the |
| Hurricane Strap 36" | HS-36 | LSTA36 | LSTA/MSTA36 | coastlines – and during storms. They reinforce transition points |
| Hurricane Strap Twist 16" | HST-16 | LTS16 | LTW16 | between beams and floor systems, floor systems and frame walls, |
| Hurricane Strap Twist 18" | HST-18 | LTS18 | LTW18 | frame walls and roof systems, and they keep floor joists from moving |
| Hurricane Strap Twist 20" | HST-20 | LTS20 | LTW20 | side to side during storms. Storm Greeter utilizes Simpson Strong-Tie |
| Hurricane Diamond Tie | HDT-1 | H1 | RT15 | straps and ties. |
| Hurricane Tie Twist | HTT-1 | H2.5A | RT Series | |

| Part Name | SG Part No. | Simpson # | USP # | |
|--------------------------|-------------|-----------|---------|---|
| Joist Hanger 2x6 | JH-26 | LUS26 | HD26 | Joist Hangers Joist hangers are used for securing floor joists to beams |
| Joist Hanger 2x6 Double | JHD-26 | LUS26-2 | HD26-2 | in the floor systems of houses and decks. If you don't see a hanger |
| Joist Hanger 2x8 | JH-28 | LUS28 | HD28 | suitable to fit your needs, contact Ovante. The hanger you need will |
| Joist Hanger 2x8 Double | JHD-28 | LUS28-2 | HD28-2 | be added to the product line and shipped to you ASAP. |
| Joist Hanger 2x10 | JH-210 | LUS210 | HD210 | |
| Joist Hanger 2x10 Double | JHD-210 | LUS210-2 | HD210-2 | |
| Joist Hanger 2x12 | JH-212 | LUS212 | HD212 | |
| Joist Hanger 2x12 Double | JHD-212 | LUS212-2 | HD212-2 | |

| Part Name | SG Part No. | |
|--------------------------|-------------|---|
| Gusset Plate 3 1/8" x 5" | GP-385 | <u>Gusset Plate</u> For reinforcing wood to wood connections in all areas of structures. |

The same polyceramic coating applied to Stinger Nails can be applied to any shape, size, or type of screw, nut, or bolt.

| Part Name | SG Part No. | | | |
|--|--------------|---|--|--|
| 12p Spiral Decking Nails Coated - 1lb box | SPNAIL-12-1 | Stinger Nails are galvanized nails coated with a tough polyceramic coating. During the nailing process, the polymer warms up and bonds with the wood | | |
| 12p Spiral Decking Nails Coated - 5lb box | SPNAIL-12-5 | | | |
| 12p Spiral Decking Nails Coated - 50lb box | SPNAIL-12-50 | Stinger Nails will not rust or corrode and you will not experience rust streaks | | |
| | | and stains on your decks, piers, or siding. | | |
| 8p Spiral Decking Nails Coated – 1lb box | SPNAIL-8-1 | | | |
| 8p Spiral Decking Nails Coated - 5lb box | SPNAIL-8-5 | One of the leading hot-dip galvanized nail manufacturers in the world has | | |
| 8p Spiral Decking Nails Coated - 50lb box | SPNAIL-8-50 | this disclaimer as part of their "warranty": | | |
| | | | | |
| 12p Ring Shank Decking/Siding Nails - 1lb box | RSNAIL-12-1 | "these nails have been Double Dipped in molten zinc by our exclusive | | |
| 12p Ring Shank Decking/Siding Nails - 5lb box | RSNAIL-12-5 | process. These nails are further warranted against red rust for the lifetime of | | |
| 12p Ring Shank Decking/Siding Nails - 50lb box | RSNAIL-12-50 | your project when used in routine, residential applications not exposed to | | |
| | | salt-spray or other extremely corrosive environments. " | | |
| Joist Hanger Nails Coated - 1lb box | JHNAIL-1 | What kind of warranty is that? Use StingerNails where ever you want to use | | |
| Joist Hanger Nails Coated - 5lb box | JHNAIL-5 | them, without worry. | | |
| Joist Hanger Nails Coated - 50lb box | JHNAIL-50 | | | |

Plumbing, Electrical & HVAC Applications

| Part Name | SG Part No. | |
|--------------------------|-------------|--|
| 1/4" Hanger Rod 36" long | HR-36 | Hanger Rods 1/4" galvanized hanger rods are used for suspending plumbing and conduit beneath slabs |
| 1/4" Hanger Rod 48" long | HR-48 | and between floors. Storm Greeter hanger rods will not rust or corrode within the slab or beneat |

| Part Name | SG Part No. | |
|-----------------------|-------------|---|
| Reinforcing Strap 18" | RS-18 | Reinforcing Straps Reinforcing - or P - straps are for suspending plumbing, conduit, and ductwork |
| Reinforcing Strap 24" | RS-24 | beneath structures, in crawlspaces, and between ceilings and upper floors. They may be bent, |
| Reinforcing Strap 36" | RS-36 | twisted and cut to length with no worries of rust or corrosion. |
| Reinforcing Strap 48" | RS-48 | |

Insulated Concrete Foundation Applications

| Part Name | SG Part No. | Simpson # | USP # | |
|-----------------------|-------------|------------|-------|---|
| Mounting Plate - ICF | MPICF | ICFVL | N/A | ICF Brackets/Ledgers - Insulated Concrete Foundations - formed with |
| Installation | | | | Styrofoam blocks – utilize the mounting plate to provide an anchor to which the ledger brackets are attached. The mounting bracket is inserted through |
| Wood Ledger Bracket – | WLICF | ICFVL-W or | N/A | the Styrofoam and will be embedded in the concrete. The chemicals in the |
| ICF Installation | | CW | | concrete immediately begin to eat away at the galvanizing, and eventually, |
| | | | | the bracket itself. |

